



Fuel filtering units for refineries

AFT – 2920-2-S

(АФТ – 2920-2-С)

Function: water separation and filtration of fuel with a high level of input contamination. Pumping is carried out by external controllable pumps. Complete automation and dispatching of the work process.



RESEARCH AND TESTING, DESIGN AND MANUFACTURE, INSTALLATION
AND ADJUSTMENT OF FUELING AND FILTRATION EQUIPMENT

AGGREGATE



Komsomolskaya str. 12b, Chekhov, Russia, 142307, www.agregatnpo.ru
tel.: +7 496 723 723 5, fax: +7 496 723 723 7, info@agregatnpo.ru



AFT - 2500-3-S (АФТ - 2500-3-С)

Function: water separation and filtration of fuel with an average level of input contamination.
Pumping is carried out by external controllable pumps.

RESEARCH AND TESTING, DESIGN AND MANUFACTURE, INSTALLATION
AND ADJUSTMENT OF FUELING AND FILTRATION EQUIPMENT

AGGREGATE



AFT - 1500-2-S (АФТ - 1500-2-С)

Function: water separation and filtration of fuel with a high level of input contamination.
Pumping is carried out by external controllable pumps.



**RESEARCH AND TESTING, DESIGN AND MANUFACTURE, INSTALLATION
AND ADJUSTMENT OF FUELING AND FILTRATION EQUIPMENT**

AFT – 1890 (АФТ – 1890)

Function: Water separation and filtration of fuel with an average level of input contamination.
Pumping is carried out by external controllable pumps.





**RESEARCH AND TESTING, DESIGN AND MANUFACTURE, INSTALLATION
AND ADJUSTMENT OF FUELING AND FILTRATION EQUIPMENT**

AFT – 360-3-S (АФТ – 360-3-С)

Function: water separation and filtration of fuel with a high level of input contamination. Pumping is carried out by the unit's own controllable pumps.



AFT – 1500-3-S (АФТ – 1500-3-С)

Function: water separation and filtration of fuel with a low level of input contamination. Pumping is carried out by external controllable pumps.





**RESEARCH AND TESTING, DESIGN AND MANUFACTURE, INSTALLATION
AND ADJUSTMENT OF FUELING AND FILTRATION EQUIPMENT**

A G R E G A T E

AFT – 480-3-S (АФТ – 480-3-С)

Function: water separation and filtration of fuel with an average level of input contamination. Pumping is carried out by external controllable pumps.
Container-type 50*50



AFT – 560-3-S (АФТ – 560-3-С)

Function: water separation and filtration of fuel with a very low level of input contamination. Pumping is carried out by external controllable pumps.
Container-type 50*50.





**RESEARCH AND TESTING, DESIGN AND MANUFACTURE, INSTALLATION
AND ADJUSTMENT OF FUELING AND FILTRATION EQUIPMENT**

A G R E G A T E



Fuel filtering unit.

AFT - 2500-3-S (АФТ - 2500-3-С)

Detached modular blocks in transport packaging.

Fuel filtering unit.

AFT - 1000-3-S (АФТ - 1000-3-С)

A detached modular block consisting of a micro-filter, water separator, and an eliminator in the fuel flow.



Komsomolskaya str. 12b, Chekhov, Russia, 142307, www.agregatnpo.ru
tel.: +7 496 723 723 5, fax.: +7 496 723 723 7, info@agregatnpo.ru